

# HiTRON

## ON-BOARD DC-DC CONVERTER ENCAPSULATED MODULES 15 WATTS SINGLE & DUAL OUTPUT HDM14-S & HDM14-D SERIES



### FEATURES:

- VERY LOW PROFILE 7.0 MM HIGH.
- SINGLE & DUAL OUTPUT.
- 2:1 INPUT RANGE.
- 15W ISOLATED OUTPUT.
- SIX-SIDED METAL SHIELD.

### SPECIFICATION

#### INPUT SPECIFICATION

**Input Range:** 2:1 DC input range.  
See Ratings Chart.

**Input Voltage:** Nominal 12/24/48Vdc.

**Input Current:** Various with input range & load. See Ratings Chart.

**Input Fuse:** Use external fuse.

**Input Filter:** Pi-Network.

**Undervoltage Shutdown:** 8Vdc.

**Isolation Resistor:** 1,000 Mega Ohms.

**Isolation Voltage:** 1,500Vdc.

**EMI:** Six-sided metal shielding.

**Remote On/Off:** TTL/CMOS-Compatible Input Control.  
Logic input reference to -input/-Vin..  
Logic [1]/Open(or 2.5-7.0Vdc above -Vin)=ON.  
Logic [2]/Short(or 0-0.08Vdc above -Vin)=OFF.

#### OUTPUT SPECIFICATION

**Output Voltage:** See Ratings Chart.

**Output Current:** See Ratings Chart.

**Voltage Accuracy:** Main O/P  $\pm 2.0\%$  typ.

**Line Regulation:**  $\pm 0.5\%$  typ.

**Load Regulation:** Single  $\pm 1.0\%$  typ.  
Dual  $\pm 2.0\%$  typ.

**Noise & Ripple:** Typ. 100mV for 3.3V/5.0V & 1.0% for others peak to peak.

**OVP:** Built-in on main output.

**Adjustability:** Not available.

**Short Circuit Protection:** Power fold back, Self-recovering.

**Overload Protection:** About 130% of overrange foldback type.

#### GENERAL SPECIFICATION

**Efficiency:** Typ.81% various with input.

**Switching Frequency:** Fixed frequency 450K Hz.

**Circuit Topology:** 450K Hz. Forward Circuit.

**Transient Response:** Full to 1/2 load <200  $\mu$ Sec.

**Case:** Black coated aluminum with non-conductive metal base.

**Weight:** 20.0g ( 0.71Oz.)

**Power Density:** 25.8Watts./ Cubic inch.

**Operating Temperature:** -40°C to +85°C range. -25°C to +71°C @ full load without derating. Derating linearly 3.5%/°C from +71°C @ full load to +85°C @ half-load.

**Storage Temperature:** -55°C to +110°C.

**Humidity:** Up to 95% RH, Non-condensing.

**Temperature Coefficient:** 0.02% /°C.

**Cooling:** Convection cooling up to 60°C @F-L. At least 100LFM moving air is recommended for F-L >+60°C in a confined area.

**Commercial Grade:** Full load up to +71°C with moving air.

**Industrial Grade:** +71 to +85°C F-L to H-L with moving air.

NOTE:(1) All measurements are at nominal input, full load and +25°C unless otherwise specified.

(2) Line Regulation measured from High to Low Lines at full load.

(3) Load Regulation measured from Full Load (F-L) to Half-Load (H-L) at nominal input.

(4) Correct fuse size by calculating the max. DC current drain at low Line input & Load and then adding 20-25% for the desired fuse size.

## INPUT/ OUTPUT & VOLTAGE/ CURRENT RATINGS CHART

### SINGLE OUTPUT


MODEL NO.	INPUT Vdc	INPUT CURRENT		OUTPUT VO1(Vdc)		CASE SIZE
		N.L. (mA)	F.L.			
HDM14-12B-S03	9.0- 18.0	30	1170	3.3V	3.00A	DM1A
HDM14-12B-S05	9.0- 18.0	30	1540	5.0V	3.00A	DM1A
HDM14-12B-S09	9.0- 18.0	30	1530	9.0V	1.66A	DM1A
HDM14-12B-S12	9.0- 18.0	30	1530	12.0V	1.25A	DM1A
HDM14-12B-S15	9.0- 18.0	30	1530	15.0V	1.00A	DM1A
HDM14-24B-S03	18.0- 36.0	20	580	3.3V	3.00A	DM1A
HDM14-24B-S05	18.0- 36.0	20	770	5.0V	3.00A	DM1A
HDM14-24B-S09	18.0- 36.0	20	765	9.0V	1.66A	DM1A
HDM14-24B-S12	18.0- 36.0	20	765	12.0V	1.25A	DM1A
HDM14-24B-S15	18.0- 36.0	20	765	15.0V	1.00A	DM1A
HDM14-48B-S03	36.0- 72.0	20	290	3.3V	3.00A	DM1A
HDM14-48B-S05	36.0- 72.0	20	385	5.0V	3.00A	DM1A
HDM14-48B-S09	36.0- 72.0	20	383	9.0V	1.66A	DM1A
HDM14-48B-S12	36.0- 72.0	20	383	12.0V	1.25A	DM1A
HDM14-48B-S15	36.0- 72.0	20	383	15.0V	1.00A	DM1A

### DUAL OUTPUT

MODEL NO	INPUT Vdc	INPUT CURRENT		OUTPUT(Vdc)		OUTPUT(A)		CASE SIZE
		N.L. (mA)	F.L.	+VO1	-VO2	+VO1	-VO2	
HDM14-12B-D03	9.0- 18.0	40	1170	+3.3V	-3.3V	1.50A	1.50A	DM1A
HDM14-12B-D05	9.0- 18.0	40	1560	+5.0V	-5.0V	1.50A	1.50A	DM1A
HDM14-12B-D12	9.0- 18.0	40	1550	+12.0V	-12.0V	0.63A	0.63A	DM1A
HDM14-12B-D15	9.0- 18.0	40	1550	+15.0V	-15.0V	0.50A	0.50A	DM1A
HDM14-24B-D03	18.0- 36.0	30	585	+3.3V	-3.3V	1.50A	1.50A	DM1A
HDM14-24B-D05	18.0- 36.0	30	780	+5.0V	-5.0V	1.50A	1.50A	DM1A
HDM14-24B-D12	18.0- 36.0	30	775	+12.0V	-12.0V	0.63A	0.63A	DM1A
HDM14-24B-D15	18.0- 36.0	30	775	+15.0V	-15.0V	0.50A	0.50A	DM1A
HDM14-48B-D03	36.0- 72.0	20	293	+3.3V	-3.3V	1.50A	1.50A	DM1A
HDM14-48B-D05	36.0- 72.0	20	390	+5.0V	-5.0V	1.50A	1.50A	DM1A
HDM14-48B-D12	36.0- 72.0	20	390	+12.0V	-12.0V	0.63A	0.63A	DM1A
HDM14-48B-D15	36.0- 72.0	20	390	+15.0V	-15.0V	0.50A	0.50A	DM1A

### MECHANICAL DIMENSIONS: MM [INCHES]

Weight: 20.0g ( 0.71Oz.)



CASE SIZE: DM1A

### PIN ASSIGNMENT

PIN NO.	SINGLE	DUAL
PIN #1.	Remote ON/OFF	Remote ON/OFF
PIN #2.	- INPUT/-Vin	- INPUT/-Vin
PIN #3.	+ INPUT	+ INPUT
PIN #4.	DC-COM	- VO2
PIN #5.	NC	DC-COM
PIN #6.	VO1	+VO1