

HiTRON

AC/DC EXTERNAL DESKTOP ADAPTER UNIVERSAL INPUT SINGLE & MULTIPLE OUTPUT 24-26 WATTS SWITCHING POWER SUPPLIES HES24 SERIES



FEATURES:

- UNIVERSAL INPUT
- DESKTOP IEC320 AC RECEPTACLE
- MEET UNIVERSAL SAFETY STANDARDS
- EMI MEET EN 55022/ FCC CLASS B
- CE MARKING COMPLIANCE

SPECIFICATION

INPUT SPECIFICATION

Input Voltage: 90-264Vac typical.
Input Connector: IEC320-3P DT7 type
AC inlet receptacle.
Input Frequency: 47-63Hz.
Inrush Current: 25A @230Vac typical.
Input Current: 0.34A @115Vac typical.
0.17A @230Vac typical.
Dielectric Withstand: Meet IEC950.
EMI: Meet EN 55022 / FCC Class B.
Hold-up Time: 15mS @115Vac typical.
60mS @230Vac typical.

OUTPUT SPECIFICATION

Output Voltage: See Ratings Chart.
Output Current: See Ratings Chart.
Output Wattage: 24-26 Watts typical.
Output Connector & Cord: Optional.
Line Regulation: 0.1-0.2% typical.
Load Regulation: Main O/P VO1 $\pm 1.5-3.0\%$ typical.
Aux. O/P VO2 $\pm 2.5-4.0\%$ typical.
Aux. O/P VO3 $\pm 3.0-6.0\%$ typical.
Noise & Ripple: 1.0% typical peak to peak.
OVP: Built-in on main VO1 only Zener diode clamping.
Overload Protection (OLP):
Fully protected against output overload and short circuit.
OLP set at about 125-150% rating output wattage.
Consult the factory for OLP setting.

GENERAL SPECIFICATION

Efficiency: 78% typical.
Switching Frequency: Approximate 60K Hz.
Circuit Topology: Fixed Frequency Flyback circuit.
Transient Response: Output voltage returns in less than
3mS following a 25% load change.
Safety Standard: UL1950/EN60950 Class I.
Power Density: 1.89 Watts / Cubic inch.
Operating Temperature: 0 to +40°C with no derating.
Storage Temperature: -20 to +85°C.
Temperature Coefficient: 0.04%/°C typical.
Cooling: Free air convection.
Construction: Impact resistant thermo-plastic
enclosure case.
Desktop Format.

NOTE: (1) All measurements are at nominal input, full load, and +25°C unless otherwise specified.

(2) Load regulation is measured at 115Vac or 230Vac in percentage to indicate the change in output voltage as the load is varied from half load to full load (unit $\pm\%$).
For the multi-output, the main output remains 50% load and other aux. output remains 20% load.

(3) The exact obtainable load regulation depends upon the output load current & cord selected. Upper data are for 6 ft. (2 m) cord AWG#18 wires.




For the details of safety approval, please consult the factory.

Due to requests in market and advances in technology, specifications subject to change without notice.

MODEL NO. DESCRIPTION: HES24 - XXX YY - N2N3

[NULL] FOR SINGLE OUTPUT
 [A]+5V, [B]+12V, [C]+15V, [D]+18V, [E]+24V,
 [F]-5V, [G]-12V, [H]-15V, [I] -18V, [J] -24V



OUTPUT VOLTAGE/CURRENT RATINGS CHART

SINGLE OUTPUT

DEFINED OUTPUT VOLTAGE (Vdc)	OUTPUT VOLTAGE(Vdc)/CURRENT (A)
5.0Vdc ≤ Any Voltage ≤ 15.0Vdc	5.0V/4.0A, 5.5V/3.7A, 6.0V/3.5A, 6.5V/3.2A, 7.0V/3.0A, 7.5V/2.7A, 8.0V/2.5A, 8.5V/2.4A, 9.0V/2.3A, 9.5V/2.2A, 10.0-11.0V/2.1A, 11.5-12.0V/2.0A, 13.0V/1.8A, 13.5-14.0V/1.7A, 14.5-15.0V/1.6A.
15.0Vdc < Any Voltage ≤ 30.0Vdc	15.5-16.0V/1.5A, 16.5-17.0V/1.4A, 17.5-18.0V/1.3A, 18.5-20.0V/1.2A, 20.5-22.0V/1.1A, 22.5-24.0V/1.0A, 24.5-26.5V/0.9A, 27.0-30.0V/0.8A.

Note: Refer to the upper Chart, or specify the V/A ratings and consult factory for the exact Model No.

SINGLE OUTPUT (Model No. for example)

MODEL NO.	OUTPUT VOLT.	OUTPUT AMP.
HES24-05040	5.0V	4.0A
HES24-07527	7.5V	2.7A
HES24-12020	12.0V	2.0A
HES24-15016	15.0V	1.6A
HES24-18013	18.0V	1.3A
HES24-24010	24.0V	1.0A
HES24-30008	30.0V	0.8A

DUAL OUTPUT

OUTPUT RAIL	OUTPUT VOLT.(Vdc)/ AMP.(A)
Main O/P VO1 ★	5-24V/2.0-0.5A. Max.Watts.10 ~12W
Aux. O/P ±VO2	±5,12,15,18,24V/2.0-0.5A. Max.Watts.12 ~18W

DUAL OUTPUT (Model No. for example)

MODEL NO.	MAIN O/P VO1★ (Vdc) (A)	AUX. O/P VO2 (Vdc) (A)
HES24-05015-B	+5.0V 1.5A	+12.0V 1.5A
HES24-12010-G	+12.0V 1.0A	-12.0V 1.0A
HES24-15008-H	+15.0V 0.8A	-15.0V 1.2A
HES24-24005-G	+24.0V 0.5A	-12.0V 1.0A

Symbol: "★" OVP built-in. " || " Double feedback

TRIPLE OUTPUT

OUTPUT RAIL	OUTPUT VOLT. (Vdc)/ AMP.(A)
Main O/P VO1 ★	+5-20V/3.0-0.60A. Max. Watts:12- 15.0W
Aux. O/P +VO2	+5,12,15,18,24V/1.2-0.25A. Max. Watts: 6.0W
Aux. O/P -VO3	-5,12,15,18,24V/0.6-0.125A. Max. Watts: 3.0W

TRIPLE OUTPUT (Model No. for example)

MODEL NO.	MAIN O/P VO1★ (Vdc) (A)	AUX. O/P VO2 (Vdc) (A)	AUX. O/P VO3 (Vdc) (A)
HES24-05030-BG	+5.0V 3.0A	+12.0V 0.50A	-12.0V 0.250A
HES24-05030-BH	+5.0V 3.0A	+12.0V 0.50A	-15.0V 0.200A
HES24-05030-EJ	+5.0V 3.0A	+24.0V 0.25A	-24.0V 0.125A

Symbol: "★" OVP built-in. " || " Double feedback.

MECHANICAL DIMENSIONS: MM [INCHES]

WEIGHT: 330.0g (11.6 Oz.)

