

HiTRON

UNIVERSAL INPUT AC-DC MEDICAL & ITE APPLICATION EXTERNAL DESKTOP SWITCHING ADAPTER 40 WATTS GREEN POWER SINGLE OUTPUT HEMG40 SERIES



FEATURES:

- ACCOMMODATE UNIVERSAL AC INPUT
- MEET MEDICAL STANDARDS IEC60601-1 & ITE STANDARDS IEC60950-1
- EMI MEET EN 55011 & EN55022 / FCC CLASS B
- MEET ENERGY STAR LEVEL V & CEC LEVEL IV
- CE MARKING COMPLIANCE

SPECIFICATION

INPUT SPECIFICATION

Input Voltage: Typical 90-264Vac.
Input Connector: 3 pole AC inlet IEC320-C14(DT7) /
2 pole AC inlet IEC320-C8(DT8).
Input Frequency: 47-63Hz.
Inrush Current: 7.5Arms (63.5Apk) at 230Vac.
Input Current: Typical 0.58A at 115Vac/ 0.337A at 230Vac.
Dielectric Withstand: Meet IEC60601-1 & IEC60950-1.
EMI: Meet EN55011 & EN55022 / FCC Class B.
Hold-up Time: Typical 17mS at 115Vac.
Typical 88mS at 230Vac.
Earth Leakage Current (Class I) : Less than 0.3 mA.
Touch Leakage Current (Class I & II) : Less than 0.1mA.
No Load Power: Less than 0.3W at 230Vac.

OUTPUT SPECIFICATION

Output Voltage: See Ratings Chart.
Output Current: See Ratings Chart.
Output Wattage: Typical 40Watts.
Output Connector & Cord: Optional.
Line Regulation: Typical 0.1%.
Load Regulation: Typical $\pm 1.0\%$.
Total Regulation: Typical $\pm 2.0\%$.
Noise & Ripple: 1.0% peak to peak.
OVP: Built-in by latch circuit.
Adjustability: Factory set.
Over Current Protection (OCP):
Fully protected against output overload and short circuit.
The PSU will shut down after OCP is activated.
Consult the factory for OCP setting.

GENERAL SPECIFICATION

Efficiency: Typical 88%
Switching Frequency: Typical 65KHz.
Circuit Topology: Fixed Frequency Flyback circuit.
Transient Response: Output voltage returns in less than
0.3mS following a 250% load change.
Safety Standard: Meet Medical IEC60601-1 & ITE
IEC60950-1, Class I for DT7(C14)

Operating Temperature: 0°C to +40°C.
Storage Temperature: -20 to +85°C.
Cooling: Free air convection.
Construction: Impact resistant thermo-plastic
enclosure case.
Power Density: 3.19Watts. / Cubic inch.
Desktop Format.

NOTE: (1) All measurements are at nominal input, full load, and +25°C unless otherwise specified.
(2) Load regulation is measured at 115Vac or 230Vac in percentage to indicate the change in output voltage as the load varied from half load to full load ($\pm\%$).
(3) The exact obtainable load regulation depends upon the output cord selected and load current.
(4) Due to requests in market and advances in technology, specifications subject to change without notice.



In application.

OUTPUT VOLTAGE / CURRENT RATINGS CHART

SINGLE OUTPUT

MODEL NO.	AC INLET	O/P VOLTAGE	O/P CURRENT
HEMG40-S120334-7	IEC320-C14(DT7)	12.0Vdc	3.34A
HEMG40-S120334-8	IEC320-C8(DT8)	12.0Vdc	3.34A
HEMG40-S150266-7	IEC320-C14(DT7)	15.0Vdc	2.66A
HEMG40-S150266-8	IEC320-C8(DT8)	15.0Vdc	2.66A
HEMG40-S240166-7	IEC320-C14(DT7)	24.0Vdc	1.66A
HEMG40-S240166-8	IEC320-C8(DT8)	24.0Vdc	1.66A

MECHANICAL DIMENSIONS: MM [INCHES]

WEIGHT: 246.5g(8.70Oz)

